

硅片产品介绍

一站式溯源硅片服务：从硅矿到硅片

可溯源20万吨

法碳认证，低碳硅片

产品涵盖广：N型、P型、HJT



86-512-6853 3900

江苏省苏州工业园区新庆路28号协鑫能源中心

www.gcltech.com

N型产品

规格	N10DL	N10LG	N10SG	N10R	N12RD	N12
边宽	182.2*183.75mm	182.2*183.75mm	182.3*183.5mm	182.2*186.7mm	182.3*210mm	210*210mm
直角边	8.57/8.49mm	1.99mm	1.90/1.89mm	7.97/7.76mm	4.72/4.07mm	1.41mm
对角线	247mm	256mm	256mm	250mm	272mm	295mm
电阻率	0.6-1.6 ($\Omega\cdot\text{cm}$)	0.6-1.6 ($\Omega\cdot\text{cm}$)	0.6-1.6 ($\Omega\cdot\text{cm}$)	0.6-1.6 ($\Omega\cdot\text{cm}$)	0.6-1.6 ($\Omega\cdot\text{cm}$)	0.6-1.6 ($\Omega\cdot\text{cm}$)

HJT

规格	N12D	N12DH	N12L	N12LH
长边宽	211.6mm	210.1mm	211.6mm	210.1mm
短边宽	210.1mm	105.05mm	210.1mm	105.05mm
直角边	1.41mm	1.41mm	1mm	1mm
对角线	296.19mm	233.28mm	296.77mm	233.56mm
电阻率	0.3-2.1 ($\Omega\cdot\text{cm}$)	0.3-2.1 ($\Omega\cdot\text{cm}$)	0.3-2.1 ($\Omega\cdot\text{cm}$)	0.3-2.1 ($\Omega\cdot\text{cm}$)

P型产品

规格	M10D	M10DL	G12
边宽	182.2mm*182.2	182.2*183.75mm	210mm*210mm
直角边	7.72mm	8.57/8.49mm	1.41mm
对角线	247mm	247mm	295mm
电阻率	0.4-1.1 ($\Omega\cdot\text{cm}$)	0.4-1.1 ($\Omega\cdot\text{cm}$)	0.4-1.1 ($\Omega\cdot\text{cm}$)